VERDI S3

AC880BP

CE UNI EN ISO 20345:2012 S3 SRC



High shoe, water-resistant WRU leather
thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568
MIDSOLE antiperforation steel according to EN 12568
SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**
INSOLE 1000, in high density and open cells latex foam. Absorbing, antistatic and perspiring

Size 36-49 **Shoe weight** Sz 42 **gr. 550**

CERTIFICATIONS

TECHNOLOGIES AND MATERIALS

SECTORS

FARMING AND MINING
COMPONENTS AND AUTOMOTIVE
WOOD
METAL CARPENTRY
BUILDING AND HEAVY INDUSTRY
LOGISTICS AND LIGHT INDUSTRY

SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS

SRC
ANTI-SLIPPING SOLE

SRA ceramic + NaLS	HEEL>= 0,28 FLAT>= 0,32	0,39 0,36
SRB steel + glycerol	HEEL>= 0,13 FLAT>= 0,18	0,28 0,22