uvex

Safety Goggles

uvex ultravision faceguard · helmet mounted safety goggles



9301714



9301105



9301626



9301906



9301815



9301716



9301613



9301633

Please note: CA lenses do not fit the PC models and vice-versa.

uvex ultravision

- classic safety goggle suitable for a wide range of applications
- flexible face seal naturally moulds to any facial shape
- generous internal volume accommodating prescription spectacles and frame recesses to locate the side arms ensuring a comfortable fit
- indirect ventilation system increases air circulation
- length-adjustable textile or neoprene headband for a secure fit and individual adaptability
- robust polycarbonate lens with uvex's proven supravision coating technology – permanent anti-fog and scratch-resistant lens
- UV400 – 100% protection against dangerous UV radiation up to 400 nm
- also available with a cellulose acetate lens featuring anti-fog performance on the inside and UV380 protection
- a benefit: lenses can be replaced when required
- metal-free

uvex ultravision CA			
Art. no.	9301714	9301906	9301716
Replacement lens	9300517	9300956	9300517
Version	anti-fog on the inside	anti-fog on the inside, wide nose piece, particularly well suited in combination with dust masks	anti-fog on the inside, with foam layer
Standard	EN 166, EN 170	EN 166, EN 170	EN 166, EN 170
Frame	transparent grey; anthracite, blue	transparent grey; anthracite, blue	transparent grey; anthracite, blue
	W 166 34 F CE	W 166 3 F CE	W 166 34 F CE
Lens	CA clear	CA clear	CA clear
	UV380	UV380	UV380
	2C-1.2 W1 FN CE	2C-1.2 W1 FN CE	2C-1.2 W1 FN CE
Weight	116 g	130 g	118 g
Order quantity multiples	4 PC	4 PC	4 PC

uvex ultravision PC					
Art. no.	9301105	9301626	9301815	9301613	9301633
Replacement lens	9301255	9301255	9301255	9301255	9301255
Version	uvex supravision excellence	uvex supravision excellence with foam layer	uvex supravision excellence top ventilation closed	uvex supravision excellence closed ventilation (gas-proof), heat-resistant frame material	uvex supravision excellence closed ventilation (gas-proof), heat-resistant frame material
Standard	EN 166, EN 170	EN 166, EN 170	EN 166, EN 170	EN 166, EN 170	EN 166, EN 170
Frame	transparent grey; anthracite, blue	transparent grey; anthracite, blue	transparent grey; anthracite, blue	yellow; anthracite, yellow	red; black, red
	W 166 34 BT CE	W 166 34 BT CE	W 166 34 BT CE	W 166 345 BT CE	W 166 345 BT CE
Lens	PC clear	PC clear	PC clear	PC clear	PC clear
	UV400	UV400	UV400	UV400	UV400
	2C-1.2 W1 BTKN CE	2C-1.2 W1 BTKN CE	2C-1.2 W1 BTKN CE	2C-1.2 W1 BTKN CE	2C-1.2 W1 BTKN CE
Weight	131 g	134 g	131 g	133 g	133 g
Order quantity multiples	4 PC	4 PC	4 PC	4 PC	4 PC

CO_2 footprint:
0.60/0.80 kg CO_2e 01/2023
(9301105, 9301815),
calculation method see page 20

MADE IN GERMANY